

MANUAL LOADER



Available Size : Panel Mounted 96 X 48, 48 X 96 LED Display (0-10 V or 4-20 mA), 0- 200 mV DC

FEATURE

- ✦ Input Impedance 150 Ohms.
- ✦ 4-20 or 0-10v PROCESS Output.
- ✦ Full range & step UP AND DOWN facility.
- ✦ 4 Digit 12.5 mm Size LCD Display.
- ✦ 230v/ 110V As or 24VDC Powered supply.
- ✦ Range/Decimal Point selectable through jumpers.
- ✦ Zero span adjustable up to 10% of the range.
- ✦ Power supply : 230V / 110V AC. Or 24V / 12V DC

TECHNICAL SPECIFICATION :

OUTPUT	1 Nos 4-20 mA (Analog Outputs)
OUTPUT LOAD	Up to 150 Ohms
CONTROL KEYS	4 (Up, Down, Enter, M) M Mode For Programing
	Up And Down Keys Used To Vary The Output In The Manual Mode
	Enter :Direct 4 or 20mA/V Selection
INDICATION	4 Digit Green/Red LED Seven Segment.
ACCURACY	Display Accuracy Of 0.15% Of Full Span, Output Accuracy Of 0.15% Of Full Span
PROGRAMMABLE PARAMETER	Control Output / Tracking Time
	Through 4 Tactile Keys
OTHER	Mounting : Panel Mounted
	(A) Supply Voltage : 110/230 V AC, 50/60 Hz (B) Power Consumption : 4 Watts Maximum
	Operating Ambient Temperature : 0~50 C, And Humidity : Below 90%, Non Condensing

ORDERING INFORMATION :

UT-401		1	2	3
OUTPUT				
4-20 mA DC	N			
0-10 V DC	R			
0-200 m V	S			
TPS				
24 V DC	N			
12 V DC	R			
10 V DC	S			
Power				
24 V DC		4		
230 V AC		2		
110 V AC		1		